

Secvest Hybrid module Set magnetic contact

Art. no. FUM050220

Page 1 of 2



Technical Data:

Dimensions	310x220x160 mm
Width	220 mm
Gross weight	1,303 kg

Height	160 mm
Length	310 mm
Net weight	1,1 kg

Secvest Hybrid module

Installation	Surface mounted
Dimensions	(LxWxH) 136x227x45 mm
Number of wired zones	10 x FSL/DEOL or 5 x CC
Type of inputs	Voltage
Outputs	4 x Relays (max. 24 V AC rms or 30 V DC)
Width	136 mm
Gross weight	0,62 kg
Radio frequency	868,6625 MHz
Transmission power	10 mW
Housing material	PC/ABS
Height	45 mm
Length	227 mm
Max. operating temperature	40 °C
Max. humidity	75 %
Max. receiving range (outdoors)	500 m

Max. sending range (outdoors)	500 m
Min. operating temperature	-10 °C
Net weight	0,48 kg
Configuration	Directly at the alarm control panel or via web server
Tamper monitoring	Yes
IP protection class	30
Voltage monitoring	Yes
DC voltage supply	10,5 - 15 V
Language of instructions	DE,EN,FR,NL,DK,IT
Power consumption	100 mA
Transmission path	Wireless
Environmental class	II

Secvest Hybrid module Set magnetic contact

Art. no. FUM050220

Page 2 of 2

Opening Detector, 4 m, 4-core (white)

EN	Grade 2
VdS class	B
Approval no.	G 105519
Dimensions	(WxHxD) 11x12x48 mm
Connections	NC, max. contact capacity 24 V DC / AC / 0.2 A / 4.8 W
Width	11 mm
Type of detection	Magnetic field measurement
Stray-field protection	No
Housing material	ABS
Height	12 mm
Cable type	4-core

Cable length	4 m
Length	48 mm
Max. operating temperature	55 °C
Min. operating temperature	-40 °C
Installation location	Integration / surface mounting
Tamper monitoring	Yes
Sensor type	Reed contact
Environmental class	IIIa
Certifications	VdS, EN 50131 Grade 2

International Switching-Mode Power Supply 13,8 V/1,75 A (Cord)

Output voltage DC	13,8 V
Dimensions	(W x H x D) about 46 x 80 x 38 mm
Input voltage AC	230 V
Housing material	ABS (white)
Cable length	1,5 m
Max. operating temperature	40 °C

Max. humidity	90 %
Min. operating temperature	0 °C
Net weight	0,16 kg
AC voltage supply	100 - 240 V
DC voltage supply	13,8 V
Power consumption	1,75 mA