

Secvest Wireless Window Handle FG 350 E (white)

Art. no. FUFT50040W Page 1 of 2



- · Greater security thanks to lock monitoring
- Reliably transmits the status of the window ("open" or "closed") to the alarm panel
- Simple installation by replacing the existing window handle

Efficient locking without the risk of false alarms – only from ABUSThe Secvest wireless window handle uses magnetic field sensors to detect any unauthorised opening of the windows. If the window is opened while it is armed by the alarm system, a message is immediately sent to the Secvest wireless alarm system. The current status of the window ("open" or "closed") is constantly transmitted wirelessly to the alarm panel, where the status display indicates that the window is open. The window is only considered "closed" by the system once it has been locked, ensuring reliable alarm triggering when a break-in occurs and minimising the risk of false alarms. Quick and easy installation without drillingThe wireless window handle is installed very easily by replacing the existing handle, without having to drill in additional holes. The handle is available in white, brown and silver.



Secvest Wireless Window Handle FG 350 E (white)

Art. no. FUFT50040W Page 2 of 2

Technical Data:

| white |
|----------------------------|
| other |
| H 112005 |
| (WxHxD) 33x168x53 mm |
| 1x lithium 1/2 AA, ER14250 |
| 33 mm |
| Magnetic switch |
| 868,6625 MHz |
| 10 mW |
| 168 mm |
| Secvest, BUM060040 |
| 53 mm |
| 55 °C |
| |
| |

| Min. operating | -10 °C |
|-----------------------|--------------------|
| temperature | |
| Modulation | FM |
| Installation location | Windows and French |
| | windows |
| Net weight | 0,55 kg |
| Tamper monitoring | Yes |
| Screw distance | 43 mm |
| Sensor type | Reed contact |
| Voltage monitoring | Yes |
| DC voltage supply | 3,6 V |
| Environmental class | П |
| Certifications | VdS home |
| | |